



◆ SPECIFICATION

Model NO.	AC03
Camera	
Image Sensor	1/2.9" CMOS sensor
Resolution	2MP 1080P
Effective Pixels	1920(H)*1080(V)
Compression	H.265
Electronic Shutter Time	Auto (1 / 12s~1 / 100000s)
S/N Ratio	40dB
Scanning System	Progressive
Video Output	Wireless network
Reset Button	Yes
PTZ	
Horizontal Rotation Range	/
Tilt Rotation Range	/
Guard Points	/
LENS Type	
Focus Length	3.6mm F2.0
Focus Control	Fixed
Lens Type	Fixed
Pixels	3M Pixels
Night Vision	
Infrared LED	14μ x 4PCS +14μ x 3PCS White light

Infrared Distance	10M
IR Status	CDS Auto Control
IR Power On	Auto Control
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP、UDP、HTTP、DDNS、DHCP、FTP、NTP
ONVIF	Optional
P2P	Support
4G	/
POE	/
Main Stream 1	2304*1296@20fps
Main Stream 2	/
Main Stream 3	/
Sub Stream 1	640*360@20fps
Sub Stream 2	/
Sub Stream 3	/
Tri Stream	/
IE Brower	/
Smart Phone	support
Wireless	
Antena	3dbi
Hotspot	Support
Wi-Fi	Wi-Fi(IEEE802.11b/g/n)
WIFI Range	No obstacles 350m Max.
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Minimun Illumination	0.01 Lux
Image Config	YES
Corridor Pattern	/
ROI	/
Defog Mode	/
BLC	/

HDR	/
3DNR	Support
DWDR	Support
Motion Detection	Support
Privacy Masking	/
Recording Mode	SDcard
Language	Chinese、English

Function

Audio	2-Way Audio
Alarm	Motion Detection
SD Card Slot	Support Max 128G

General

Housing	plastic,IP65
Bracket	Support
IR Cut Filter	YES
Power	DC 12V/1A
Operation Temperature	-10℃ ~ +50℃ RH75% Max
Storage Temperature	-20℃ ~ +60℃ RH75% Max
Size	230(W)x170(H)x130(D)mm

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA
 Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: info@cantonk.com