



◆ SPECIFICATION

| Model NO. | AC04 |
|---------------------------|------------------------------|
| Camera | |
| Image Sensor | 1/2.9" COMS sensor |
| Resolution | 2MP 1080P |
| Effective Pixels | 1920(H)*1080(V) |
| Compression | H.265 |
| Electronic Shutter Time | Auto (1 / 12s~1 / 100000s) |
| S/N Ratio | 40dB |
| Scanning System | Progressive |
| Video Output | Wireless network |
| Reset Button | Yes |
| PTZ | |
| Horizontal Rotation Range | 0~270° |
| Tilt Rotation Range | 0~90° |
| Guard Points | Optional,Max 6 points |
| LENS Type | |
| Focus Length | 2.8mm F2.0 |
| Focus Control | Fixed |
| Lens Type | Fixed |
| Pixels | 2M Pixels |
| Night Vision | |
| Infrared LED | 14μ x 8PCS |

| | |
|------------------------|-----------------------------------|
| Infrared Distance | 10-15m (Depending On Environment) |
| IR Status | CDS Auto Control |
| IR Power On | Auto Control |
| Network | |
| Ethernet | RJ-45 (10/100Base-T) |
| Protocol | TCP/IP、UDP、HTTP、DDNS、DHCP、FTP、NTP |
| ONVIF | Optional |
| P2P | Support |
| 4G | / |
| POE | / |
| Main Stream 1 | 1920*1080@25fps |
| Main Stream 2 | / |
| Main Stream 3 | / |
| Sub Stream 1 | 640*480@25fps |
| Sub Stream 2 | / |
| Sub Stream 3 | / |
| Tri Stream | / |
| IE Brower | / |
| Smart Phone | support |
| Wireless | |
| Antena | 3dbi |
| Hotspot | Support |
| Wi-Fi | Wi-Fi(IEEE802.11b/g/n) |
| WIFI Range | No obstacles 350m Max. |
| Camera Features | |
| Day/Night | Color/ B&W (IR-CUT) |
| Minimun Illumination | 0.01 Lux |
| Image Config | YES |
| Corridor Pattern | / |
| ROI | / |
| Defog Mode | / |
| BLC | / |

| | |
|------------------|------------------|
| HDR | / |
| 3DNR | Support |
| DWDR | Support |
| Motion Detection | Support |
| Privacy Masking | / |
| Recording Mode | SDcard |
| Language | Chinese, English |

Function

| | |
|--------------|------------------|
| Audio | 2-Way Audio |
| Alarm | Motion Detection |
| SD Card Slot | Support Max 128G |

General

| | |
|-----------------------|-------------------------|
| Housing | plastic, IP65 |
| Bracket | Support |
| IR Cut Filter | YES |
| Power | DC 12V/1A |
| Operation Temperature | -10°C ~ +50°C RH75% Max |
| Storage Temperature | -20°C ~ +60°C RH75% Max |
| Size | 195(W)x100(H)x190(D)mm |

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA
 Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: info@cantonk.com