

SPECIFICATION

Model NO.

Package

NVR

Camera

WIFI Range

Cable

Mouse

Adaptor

Weight

Camera Model

Camera

Image Sensor

Resolution

Effective Pixels

Compression

TV System

Electronic Shutter Time

S/N Ratio

Scanning System

Video Output

Reset Button

LENS Type

Focus Length

Focus Control

Lens Type

Pixels

Night Vision

Infrared LED

Infrared Distance

IR Status

IR Power On

Network

Ethernet

Protocol

ONVIF

P2P

POE

Main Stream 1

Main Stream 2

Main Stream 3

Sub Stream 1

Sub Stream 2

Sub Stream 3

Tri Stream

IE Brower

Smart Phone

Wireless

Antena

Hotspot

Wi-Fi

WIFI Range

Camera Features

Day/Night
Image Config
Corridor Pattern
ROI
Defog Mode
BLC
HDR
WDR
Motion Detection
Privacy Masking
Recording Mode
Language

Interface

Audio
Alarm
SD Card Slot
RS485

General

Housing
Anti-cut Bracket
IR Cut Filter
Operation Temperature
Storage Temperature
Power Source
Dimension
Weight
Model

System

Main Processor
Operating System

Video

Input

Output

Audio

Input

Output

Audio Bit Rate

Audio Compression standard

Alarm

Sensor Input

Output

Motion Detection

Trigger Events

AI Function

Face Comparison

Display

Monitor

Resolution

Display Split

Digital Zoom

OSD

Recording

Video Compression

Resolution

Record Rate

Record Mode

Playback & Backup

Local Sync Playback

Decode Capability

Remote Sync Playback

Search Mode

Playback Functions

Backup Mode

Network

Interface
Incoming Bandwidth
Network Functions
Onvif Version
Web Browser
CMS Software
Cloud Support(P2P)
Smart Phone
POE
WIFI

Storage

Interface Type
Capacity
eSATA

General

Language
USB Interface
RS485
Power Supply
Working Environment
Dimension(W×D×H)
Weight



WIFIMB4364KE200
1x NVRM4364KTW
4 x IPR25KE200W
No Obstacles 300m Max
1 x 1m Net Cable
1xUSB 2.0 Mouse
1xDC 12V 2A for WIFI NVR, 4xDC 12V 0.5A for WIFI IP Camera
7.32kg/SET
IPR25KE200W
1/2.9" Full HD CMOS Sensor
2MP 1080P
1920(H)*1080(V)
H.264/H.264+/H.265/H.265+
PAL/NTSC
Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
≥52dB
Progressive
Wireless network

Yes
3.6mm
Fixed
Fixed
2M Pixels
42μ x 2PCS
25M
Auto Control
Auto Control
/
TCP/IP,ICMP,RTP,RTSP,RTCP
/
/
/
1920*1080@1-15fps(default resolution:1920*1080/frame rate:15fps/bit rate:1Mbps)
/
/
720*480@1-15fps(default frame rate:15fps/bit rate:0.5Mbps)
/
/
/
/
/
3dbi
NO
Wi-Fi(IEEE802.11b/g/n)
No obstacles 300m Max.

Color/ B&W (IR-CUT)
Saturation/Brightness/Contrast /Sharpness, Mirror, White Balance, FLK(Flicker Control)
/
/
YES
YES
/
YES
Support
3 Rectangular Zone
NVR
/

/
/
/
/

Metal , IP67
YES
YES
-10℃ ~ +50℃ RH95% Max
-20℃ ~ +60℃ RH95% Max
DC12V±10%, 500mA
157(W) x 70(H) x 66(D)mm
650g
NVRMB4364KTW

ARM Cortex A7 Quad-core Processor
Embedded LINUX

4CH (2592x1944, 2048x1536, 1920x1080, 1280x960, 1280x720, etc)

1 VGA, 1 HD
/
Built In Speaker
64kbps
G711u, G711a, G726
NO
NO
4 Channel, MD Zones: 396 (22 × 18)
Recording, Email, FTP, Snapshot, Buzzer and Screen Tips, Alarm Output
1 channel video stream face Comparison(1 face databases with 10 face images)
Support 12 Inch Monitor Built In
1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
4CHxD1/4CHx1080P@15fps/1CHx1080P/1CHx3MP/1CHx4MP/1CHx5MP
YES
Camera Title, Time, Recording, Motion Detection, Alarm
H.264/H.265/H.264+/H.265+
5MP(2592×1944),4MP(2688×1520),3MP(2048×1536),1080P(1920×1080),960P(1280×960),720P(1280×720),D1 (720×576/720×480)
PAL : 5MP@4×25fp,4MP@4×25fp,3MP@4×25fp,1080P@4×25fp, 960P@4×25fp,720P@4×25fp, D1@4×25fp NTSC: 5MP@4×30fp,4MP@4×30fp,3MP@4×30fp,1080P@4×30fp, 960P@4×30fp, 720P@4×30fp, D1@4×30fp
Manual\Timer\Motion Detection
1CH 5MP@30fps, 1CH 4MP@30fps, 2CH 3M@30fps, 4CH 1080P@20fps, 4CH 960P@30fps, 4CH 720P@30fps
4CH 1080P@20fps
YES
ALL, Channel, Manual, Time, Date, Motion Detection
Play, Pause, Stop, Fast Play, Digital Zoom
Network/USB(With usb hub)

1 RJ45 10M/100M Adaptive Ethernet Interface
60MB
TCP/CP, HTTP, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTP, RTSP, RTCP, p2p
Support Onvif 2.4
IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
Support Windows 7/ Windows 8/Windows 10
Yes
iPhone, iPad, Android, Android Pad
/
Support, WIFI Range: No Obstacles 300m Max.

1 SATA Hard Disk Interface (2.5"SATA)
Up to 8TB capacity
/

Traditional Chinese, Simplified Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek, Vietnamese
1 USB 2.0 Interfaces
/
DC12V/2A
-10~55°C/10~90%
287(L)*142(W)*252(H)mm
1032g