



◆ SPECIFICATION

Model NO.	AC90-4G
<b>Camera</b>	
Image Sensor	1/2.9" COMS sensor
Resolution	2MP 1080P
Effective Pixels	1920(H)*1080(V)
Compression	H.265
Electronic Shutter Time	Auto ( 1 / 12s~1 / 100000s)
S/N Ratio	40dB
Scanning System	Progressive
Video Output	4G network
Reset Button	Yes
<b>PTZ</b>	
Horizontal Rotation Range	0~270°
Tilt Rotation Range	0~90°
<b>LENS Type</b>	
Focus Length	3.6mm F2.3
Focus Control	Fixed
Lens Type	Fixed
Pixels	2M Pixels
<b>Night Vision</b>	
Infrared LED	14μ x 2pcs Infrared Array + 4pcs LED White Light
Infrared Distance	10-15m (Depending On Environment)

IR Status	CDS Auto Control
IR Power On	Auto Control
<b>Network</b>	
Ethernet	/
Protocol	TCP/IP、UDP、HTTP、DDNS、DHCP、FTP、NTP
ONVIF	/
P2P	Support
4G	LTE4G-Nano SIM 、LTE-FDD:B1/3/5/8 、LTE-TDD:B38/39/40/41
POE	/
Main Stream 1	1920*1080@15fps
Main Stream 2	/
Main Stream 3	/
Sub Stream 1	640*360@15fps
Sub Stream 2	/
Sub Stream 3	/
Tri Stream	/
IE Brower	/
Smart Phone	support
<b>Wireless</b>	
Antena	/
Hotspot	/
Wi-Fi	/
WIFI Range	/
<b>Camera Features</b>	
Day/Night	Color/ B&W (IR-CUT )
Minimun Illumination	0.01 Lux
Image Config	YES
Corridor Pattern	/
ROI	/
Defog Mode	/
BLC	/
HDR	/

3DNR	Support
DWDR	Support
Motion Detection	Support
Privacy Masking	/
Recording Mode	SDcard
Language	Chinese, English

## Function

Audio	2-Way Audio
Alarm	Motion Detection 、 PIR human body infrared detection 、 Humanoid AI detection, personnel intrusion detection
SD Card Slot	Support Max 128G

## General

Housing	plastic, IP65
Bracket	Support
IR Cut Filter	YES
Power	DC 5V/2A or 18650 battery powered
Operation Temperature	0°C ~ +40°C RH95% Max
Storage Temperature	-10°C ~ +50°C RH95% Max
Size	224(W)x209(H)x139(D)mm

### Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: [info@cantonk.com](mailto:info@cantonk.com)