



◆ SPECIFICATION

Model NO.	KMBAHTC500FEHW	KMBAHTC500ESHW
Video Output Mode	AHD/TVI: 5M@20fps/12.5fps, 4M@30fps, 2M@30fps; CVI: 4M@30fps, 2M@30fps	AHD/TVI: 5M@20fps/12.5fps, 4M@30fps, 2M@30fps; CVI: 4M@30fps, 2M@30fps
Camera		
Image Sensor	1/3" CMOS Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Image Resolution	5M:2592*1944 4M:2560*1440 2M:1920*1080	5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC	PAL/NTSC
Electronic Shutter	Auto	Auto
Minimum Illumination	0.01Lux	0.005Lux
Scanning System	Progressive Scan	Progressive Scan
Lens		
Focus Length	Board Lens 6mm	Board Lens 6mm
Focus Control	Fixed	Fixed
Lens Type	Fixed	Fixed
Night Vision		
IR Cut Filter	NO	NO
Infrared LED	No,Support Warm light LED double3015Ux4	No,Support Warm light LED double3015Ux4
Light Distance	up to 40M	up to 40M
IR Status	AGC Auto Control	AGC Auto Control
Camera Features		
Starlight	/	YES
Day/Night	Color	Color
OSD Menu	YES	YES
WDR	DWDR	YES
UTC	YES	YES
Noise Reduction	DNR	AI-DNR
White Balance	AUTO / MANUAL	AUTO / MANUAL
Gain Control	AUTO	AUTO
General		
Housing	IP67	IP67
Bracket	YES	YES
Operation Temperature	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%,750mA	DC12V±10%,750mA
Dimension	93(W) x 91(H) x 263(D)mm	93(W) x 91(H) x 263(D)mm
Weight	1.45KG	1.45KG

Cantank (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA
Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantank.com> Email: info@cantank.com