



◆ SPECIFICATION

Model NO.	KMBAHD4005XESL	KMBATE4005XSH
Video Output Mode	EX-SDI: 8M@15fps, 4M/2M@30fps/25fps; HD-SDI: 2M@30fps/25fps; AHD/TVI: 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI: 4M/2M@30fps/25fps;	AHD/TVI: 5M@20fps/12.5fps, 4M@30fps, 2M@30fps; CVI: 4M@30fps, 2M@30fps; EX-SDI: 4M/2M@30fps/25fps, 2M@60fps/50fps, 2M@30fps/25fps, 720P@60fps/50fps, 720P@30fps/25fps; HD-SDI: 2M@30fps/25fps, 720P@30fps/25fps

Camera

Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080	5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC	PAL/NTSC
Electronic Shutter	Auto	Auto
Minimun Illumination	0.01Lux	0.005Lux
Scanning System	Progressive Scan	Progressive Scan

Lens

Focus Length	2.7-13.5mm Motor Zoom	2.7-13.5mm Motor Zoom
Focus Control	Auto	Auto
Lens Type	Auto	Auto

Night Vision

IR Cut Filter	YES	YES
Infrared LED	42μ x4PCS	42μ x4PCS
Infrared Distance	40M	40M
IR Status	AGC Auto Control	AGC Auto Control

Camera Features

Starlight	/	YES
Day/Night	YES	YES
OSD Menu	YES	YES
WDR	YES	YES
UTC	YES	YES
Noise Reduction	3DNR	3DNR
White Balance	AUTO / MANUAL	AUTO / MANUAL
Gain Control	AUTO	AUTO

General

Housing	IP67	IP67
Bracket	YES	YES
Operation Temperature	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%,750mA	DC12V±10%,750mA

Dimension	93(W) x 91(H) x 263(D)mm	93(W) x 91(H) x 263(D)mm
Weight	1.45Kgs	1.45Kgs

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: info@cantonk.com