



◆ SPECIFICATION

|                        |  |
|------------------------|--|
| Model NO.              | KBTA30HD800ES  |
| Video Output Mode      | EX-SDI: 8M@15fps, 4M/2M@30fps/25fps; HD-SDI: 2M@30fps/25fps;<br>AHD/TVI/CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps |
| <b>Camera</b>          |  |
| Image Sensor           | 1/2.8" SONY CMOS sensor  |
| Image Resolution       | 8M:3840*2160 4M:2560*1440 2M:1920*1080   |
| Electronic Shutter     | PAL/NTSC   |
| TV System              | Auto   |
| Minimum Illumination   | 0.01Lux  |
| Scanning System        | Progressive Scan   |
| <b>Lens</b>            |  |
| Focus Length           | Board Lens 3.6mm   |
| Focus Control          | Fixed  |
| Lens Type              | Fixed  |
| <b>Night Vision</b>    |  |
| IR Cut Filter          | YES  |
| Infrared LED           | 14μ x20PCS   |
| Infrared Distance      | 30M  |
| IR Status              | AGC Auto Control   |
| <b>Camera Features</b> |  |
| Starlight              | /  |
| Day/Night              | YES  |
| OSD Menu               | YES  |
| WDR                    | YES  |
| UTC                    | YES  |
| Noise Reduction        | 3DNR   |
| White Balance          | AUTO / MANUAL  |
| Gain Control           | AUTO   |

## General

|                       |                         |
|-----------------------|-------------------------|
| Housing               | IP67                    |
| Bracket               | YES                     |
| Operation Temperature | -10°C ~ +60°C RH95% Max |
| Storage Temperature   | -20°C ~ +60°C RH95% Max |
| Power Source          | DC12V±10%,700mA         |
| Dimension             | 170(W)x75(H)x77(D)mm    |
| Weight                | 770g                    |

### Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: [info@cantonk.com](mailto:info@cantonk.com)