



◆ SPECIFICATION

Model NO.	KLCAHD800ES
Video Output Mode	EX-SDI: 8M@15fps, 4M/2M@30fps/25fps; HD-SDI: 2M@30fps/25fps; AHD/TVI/CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps

Camera

Image Sensor	1/2.8" SONY CMOS sensor
Image Resolution	8M:3840*2160 4M:2560*1440 2M:1920*1080
Electronic Shutter	PAL/NTSC
TV System	Auto
Minimum Illumination	0.01Lux
Scanning System	Progressive Scan

Lens

Focus Length	Board Lens 6mm
Focus Control	Fixed
Lens Type	Fixed

Night Vision

IR Cut Filter	YES
Infrared LED	42μ x 2PCS
Infrared Distance	30M
IR Status	AGC Auto Control

Camera Features

Starlight	/
Day/Night	YES
OSD Menu	YES
WDR	YES
UTC	YES
Noise Reduction	3DNR
White Balance	AUTO / MANUAL
Gain Control	AUTO

General

Housing	IP67
Bracket	NO
Operation Temperature	-10°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%,500mA
Dimension	∅ 115 x 113(H) mm
Weight	800g

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: info@cantonk.com