



◆ SPECIFICATION

Model NO.	KMBAHD8004XES
Video Output Mode	EX-SDI: 8M@15fps, 4M/2M@30fps/25fps; HD-SDI: 2M@30fps/25fps; AHD/TVI/CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps
<b>Camera</b>	
Image Sensor	1/2.8" SONY CMOS sensor
Image Resolution	8M:3840*2160 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	Auto
Minimum Illumination	0.01Lux
Scanning System	Progressive Scan
<b>Lens</b>	
Focus Length	2.7-13.5mm Motor Zoom
Focus Control	Auto
Lens Type	Auto
<b>Night Vision</b>	
IR Cut Filter	YES
Infrared LED	42μ x4PCS
Infrared Distance	40M
IR Status	AGC Auto Control
<b>Camera Features</b>	
Starlight	/
Day/Night	YES
OSD Menu	YES
WDR	YES
UTC	YES
Noise Reduction	3DNR
White Balance	AUTO / MANUAL
Gain Control	AUTO

## General

Housing	IP67
Bracket	YES
Operation Temperature	-10°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%,750mA
Dimension	93(W) x 91(H) x 263(D)mm
Weight	1.45KGs

### Cantonk (guangzhou) Corporation Limited

Add. :F5, 2# Building, No. 728, Kaichuang AVE., Economic & Technological Development Zone, Luogang District, 510530 Guangzhou, China

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: [info@cantonk.com](mailto:info@cantonk.com)