



◆ SPECIFICATION

Model NO.	KBCW60HTC800ESL	KBCW60HTC800ES	KBCW60HTC800FKE
Video Output Mode	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI:8M@15fps/12.5fps, 4M/2M@30fps/25fps; TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps	AHD/TVI/CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; TVI/CVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps 4M/2M@30fps/25fps
Camera			
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor	1/2.8" SONY CMOS sensor	1/2.5" CMOS sensor
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080	8M:3840*2160 4M:2560*1440 2M:1920*1080	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC	PAL/NTSC	PAL/NTSC
Electronic Shutter	Auto	Auto	Auto
Minimum Illumination	0.005Lux	0.01Lux	0.01Lux
Scanning System	Progressive Scan	Progressive Scan	Progressive Scan
Lens			
Focus Length	Board Lens 6mm	Board Lens 3.6mm	Board Lens 3.6mm
Focus Control	Fixed	Fixed	Fixed
Lens Type	Fixed	Fixed	Fixed
Night Vision			
IR Cut Filter	YES	YES	YES
Infrared LED	42μ x4PCS	42μ x4PCS	42μ x4PCS
Infrared Distance	40M	40M	40M
IR Status	AGC Auto Control	AGC Auto Control	AGC Auto Control
Camera Features			
Starlight	/	/	/
Day/Night	YES	YES	YES/NO
OSD Menu Language	YES	YES	YES
WDR	YES	YES	DWDR

UTC	YES	YES	YES
Noise Reduction	3DNR	3DNR	DNR
Coaxial Audio	/	/	YES(only TVI)
White Balance	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL
Gain Control	AUTO	AUTO	AUTO
General			
Housing	IP67	IP67	IP67
Bracket	YES	YES	YES
Operation Temperature	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%,750mA	DC12V±10%,750mA	DC12V±10%,750mA
Dimension	162(W) x 88(H) x 86(D)mm	162(W) x 88(H) x 86(D)mm	162(W) x 88(H) x 86(D)mm
Weight	1.4kg (with bracket)	1.4kg (with bracket)	1.4kg (with bracket)

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZH
Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: info@cantonk.com