



♦ SPECIFICATION

Model NO.	KSBDTHC500FPEW
/ideo Output Mode	AHD/TVI: 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 4M@30fps/25fps, 2M@30fps/25fps
Camera	
mage Sensor	1/3" CMOS Sensor
mage Resolution	5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	Auto
Minimun Illumination	0.01Lux
Scanning System	Progressive Scan
Lens	
ocus Length	Board Lens 3.6mm
ocus Control	Fixed
ens Type	Fixed
Night Vision	
R Cut Filter	YES
nfrared LED	No,Support Warm light LED 3015U*2
ight Distance	up to 25m
R Status	AGC Auto Control
Camera Feature	25
itarlight	/
Day/Night	Color
OSD Menu	YES
WDR	DWDR
JTC	YES
Noise Reduction	DNR
Coaxial Audio	YES(only TVI)
White Balance	AUTO / MANUAL
Gain Control	АИТО
General	
Housing	IP67
Bracket	YES
Operation Temperature	-10˚C ~+60˚C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%,450mA
Dimension	154(W)x70.5(H)x70.5(D)mm
Veight	375g