



◆ SPECIFICATION

<b>Model</b>	<b>XVRCBDA1621</b>
<b>System</b>	
Main Processor	HI3521DV200
Operating System	Embedded LINUX
<b>Video</b>	
Input	Normal Mode: Analog: 16*(TVI/AHD: 5M@12fps; AHD/TVI/CVI: 4M@15fps; AHD/TVI: 3M; AHD/TVI/CVI: 1080P/720P;Analog: 960H) Analog+Network: 2*Analog(5MP)+14*network(MAX 8MP), 4*Analog(5MP)+12*network(MAX 8MP),6*Analog(5MP)+10*network(MAX 8MP), 8*Analog(5MP)+8*network(MAX 8MP),10*Analog(5MP)+6*network(MAX 8MP), 12*Analog(5MP)+4*network(MAX 8MP),14*Analog(5MP)+2*network(MAX 8MP) Network: 16*8MP/5MP/4MP/3MP/1080P/960P/720P(Total incoming bandwidth ≤80M)
Input	16CH BNC
Signal Type	Analog/AHD/CVI/TVI 2.0/TVI 3.0/Network
Output	1HD,1VGA,1CVBS
<b>Audio</b>	
Input	6 ChannelRCA,support AOC
Two-way Audio	NO
Output	1 Channel, RCA
<b>Alarm</b>	
Sensor Input	4
Output	1
Motion Detection	16 Channel
Trigger Events	Recording, Email, Screen tips, Buzzer, Push notifications(motion detection)
Email Alarm	Send Image to The Designated E-mail
<b>PTZ</b>	
Interface	RS485
Protocol	Pelco-D, Pelco-P
Baud Rate	110~921600
Address	0~255
<b>Display</b>	
VGA	Resolution: 1920 × 1080P /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz,1024 × 768 /60Hz
HD Output	Resolution: 3840x2160 1920x1080 1280x1024 1280x720 1024x768
Display Split	16 Channel/9 Channel/8 Channel/4 Channel / 1Channel
Privacy Masking	3 Rectangular Zones (Each camera)
OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording
<b>Recording</b>	
Video Compression	H.265/H.265+/H.264/H.264+

Audio Compression	G.711u/G.711a/AAC
Resolution	5MP_Lite(1296×1944),4MP_Lite(1280×1440),3MP_Lite(1024×1536),1080N(960×1080),720P(1280×720),960H(P:960×576/N:960×480)
Video Quality	Lowest/Low/Ordinary/Good/Better/Best
Record Rate	Analog: PAL: 5MP_Lite(1296×1944 16*6fps),4MP_Lite(1280×1440 16*8fps),3MP_Lite(1024×1536 16*10fps), 1080N(960×1080 16*15fps),720P(1280×720 16*15fps), 960H(960×576 16*25fps) NTSC:5MP_Lite(1296×1944 16*6fps),4MP_Lite(1280×1440 16*8fps),3MP_Lite(1024×1536 16*10fps), 1080N(960×1080 16*15fps),720P(1280×720 16*15fps), 960H(960×576 16*25fps) Pure IP(H.265): PAL :8MP@9x25fps, 5MP@12x25fps,4MP@16x25fps, 3MP@16x25fps, 1080P@16x25fps, 960P@16x25fps, 720P@16x25fps, D1@16x25fps NTSC:8MP@9x30fp, 5MP@12x30fps,4MP@16x30fps, 3MP@16x30fps, 1080P@16x30fps, 960P@16x30fps, 720P@16x30fps, D1@16x30fps
Record Mode	Manual\Timer\Motion Detection\Alarm Input

## Playback & Backup

Decode Capability	4CH 1080P@30fps
Sync Playback	Pure Analog: 16CH 960H@25fps, 16CH 720P@15fps, 16CH 1080N@15fps, 16CH 5M_LITE@6fps, 16CH 4M_LITE@8fps, 16CH 3M_LITE@10fps Mixture mode: 4CH D1@25fps, 4CH 1080P@25fps, 1CH 8MP@30fps Pure Network: 4CH D1@25fps, 4CH 1080P@25fps, 1CH 8MP@30fps
Remote Playback	4 Channel / 1Channel
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast play, Slow play, Rewind, Single frame forward/back, Digital Zoom, Full screen
Smart Phone Playback	4 Channel
Backup Mode	USB Device(with format FAT 32 )/Network/FTP

## Network

Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP,DHCP, FTP, DDNS, RTP, RTSP, RTCP
DDNS	Dyndns, changeip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE,HDPROVN,DYNAMIC_PLANET,EASY_PLANET
Web Browser	Edge,IE8-11, Google Chrome , Firefox ,Safari
CMS Software	Support Windows 7/ Windows 8/Windows 10
Extra Stream	CIF/D1(1-30fps)
Smart Phone	iPhone, ipad, Android ,Android pad

## Hard Disk Driver

Interface Type	2 SATA Interface
Capacity	1 SATA Hard Disk (2.5"/3.5" SATA, Up to 16TB)

## General

Language	Simplified Chinese,Traditional Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek, Vietnamese, Japanese
UTC Control	YES
USB Interface	2 USB 2.0 Interfaces
Power consumption	DC 12V/4A ≤6W (Without Hard Disk)
Working Environment	-10~55℃/10~90%
Dimension (W×D×H)	310*295*46(mm)
Weight	2kg (Without HDD)

### Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: [info@cantonk.com](mailto:info@cantonk.com)