



◆ SPECIFICATION

| Model NO.              | KSBDHTC800FKPW   | KSBDHTC800ESLW  | KSBDHTC800FKEW   |
|------------------------|--|---|--|
| Video Output Mode      | AHD/TVI: 8M@15fps,<br>5M@20fps/12.5fps,<br>4M/2M@30fps/25fps;<br>CVI: 8M@15fps,<br>4M/2M@30fps/25fps | AHD: 8M@15fps,<br>5M@20fps/12.5fps,<br>4M/2M@30fps/25fps;<br>CVI: 8M@15fps/12.5fps,<br>4M/2M@30fps/25fps<br>TVI: 8M@15fps/12.5fps,<br>5M@20fps/12.5fps,<br>4M/2M@30fps/25fps; | AHD: 8M@15fps,<br>5M@20fps/12.5fps,<br>4M@30fps/25fps/15fps,<br>2M@30fps/25fps;<br>TVI: 8M@15fps/12.5fps,<br>5M@20fps/12.5fps<br>4M@30fps/25fps/15fps,<br>2M@30fps/25fps;<br>CVI: 8M@15fps/12.5fps,<br>5M@20fps/12.5fps<br>4M/2M@30fps/25fps |
| <b>Camera</b>          |  |   |  |
| Image Sensor           | 1/2.5" CMOS sensor   | 1/2.8" SONY Starvis Back-illuminated CMOS sensor  | 1/2.5" CMOS sensor   |
| Image Resolution       | 8M:3840*2160 5M:2592*1944<br>4M:2560*1440 2M:1920*1080   | 8M:3840*2160 5M:2592*1944<br>4M:2560*1440 2M:1920*1080  | 8M:3840*2160 5M:2592*1944<br>4M:2560*1440 2M:1920*1080   |
| TV System              | PAL/NTSC   | PAL/NTSC  | PAL/NTSC   |
| Electronic Shutter     | Auto   | Auto  | Auto   |
| Scanning System        | Progressive Scan   | Progressive Scan  | Progressive Scan   |
| <b>Lens</b>            |  |   |  |
| Focus Length           | Board Lens 3.6mm   | Board Lens 3.6mm  | Board Lens 3.6mm   |
| Focus Control          | Fixed  | Fixed   | Fixed  |
| Lens Type              | Fixed  | Fixed   | Fixed  |
| <b>Night Vision</b>    |  |   |  |
| IR Cut Filter          | YES  | YES   | YES  |
| Infrared LED           | No,Support Warm light LED<br>3030*2  | No,Support Warm light LED<br>3030*2   | No,Support Warm light LED<br>3030*2  |
| Light Distance         | up to 25M  | up to 25M   | up to 25M  |
| IR Status              | AGC Auto Control   | AGC Auto Control  | AGC Auto Control   |
| <b>Camera Features</b> |  |   |  |
| Starlight              | /  | /   | /  |
| Day/Night              | Color  | Color   | Color  |
| OSD Menu               | YES  | YES   | YES  |
| WDR                    | /  | YES   | DWDR   |
| UTC                    | YES  | YES   | YES  |
| Noise Reduction        | 3DNR   | 3DNR  | DNR  |
| Coaxial Audio          | /  | /   | YES(only TVI )   |
| White Balance          | AUTO / MANUAL  | AUTO / MANUAL   | AUTO / MANUAL  |
| Gain Control           | AUTO   | AUTO  | AUTO   |
| <b>General</b>         |  |   |  |
| Housing                | IP67   | IP67  | IP67   |
| Bracket                | YES  | YES   | YES  |
| Operation Temperature  | -10℃ ~ +60℃ RH95% Max  | -10℃ ~ +60℃ RH95% Max   | -10℃ ~ +60℃ RH95% Max  |
| Storage Temperature    | -20℃ ~ +60℃ RH95% Max  | -20℃ ~ +60℃ RH95% Max   | -20℃ ~ +60℃ RH95% Max  |
| Power Source           | DC12V±10%,700mA  | DC12V±10%,700mA   | DC12V±10%,700mA  |
| Dimension              | 154(W)x70.5(H)x70.5(D)mm   | 154(W)x70.5(H)x70.5(D)mm  | 154(W)x70.5(H)x70.5(D)mm   |
| Weight                 | 370g   | 370g  | 370g   |

Cantonk (Guangzhou) Corporation Limited

Address: #BUILDING, NO.728 KAICHUANG AVE., ECONOMIC & TECHNOLOGICAL DEVELOPMENT ZONE, HUANGPU DISTRICT, GUANGZHOU, CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: [info@cantonk.com](mailto:info@cantonk.com)