



◆ SPECIFICATION

<b>Model</b>	<b>XVRHCT430</b>
<b>System</b>	
Main Processor	MC6630
Operating System	Embedded LINUX
<b>Video</b>	
Input	Normal Mode: Default: 4*(AHD/TVI/CVI:8M;AHD/TVI:5M,AHD/TVI/CVI:4MP/3MP/2MP/720P/960H)+2*IPC(Max5MP) Analog+Network: 2*(AHD/TVI/CVI:8M;AHD/TVI:5M,AHD/TVI/CVI:4MP/3MP/2MP/720P/960H)+7*IPC(MAX 5MP) Lite Mode: Default: 4*(TVI/AHD/CVI: 5M@12fps; AHD/TVI/CVI: 4M@15fps; AHD/TVI/CVI: 3M@18fps; AHD/TVI/CVI: 1080P/720P; Analog: 960H)+2*network(MAX 5MP) Analog+Network: 2*Analog(TVI/AHD/CVI: 5M@12fps; AHD/TVI/CVI: 4M@15fps; AHD/TVI/CVI: 3M@18fps; AHD/TVI/CVI: 1080P/720P; Analog: 960H)+7*network(MAX 5MP) Network: 16*5MP/4MP/3MP/1080P/960P/720P(Total incoming bandwidth ≤48M)
Input	4CH BNC
Signal Type	Analog/AHD/CVI/TVI 2.0/TVI 3.0/Network
Output	1HD,1 VGA, 1 CVBS
<b>Audio</b>	
Input	2 Channel, RCA
Two-way Audio	NO
Output	1 Channel, RCA
<b>Alarm</b>	
Sensor Input	4 CH
Output	1 CH
Motion Detection	4 Channel(max 16 Channel in pure network mode)
Trigger Events	Recording, Email, Screen tips, Buzzer, Push notifications(motion detection)
Email Alarm	Send Image to The Designated E-mail
<b>AI Function</b>	
Human Detection	YES
<b>PTZ</b>	
Interface	RS485
Protocol	Pelco-D, Pelco-P
Baud Rate	110~921600
Address	0~255
<b>Display</b>	
VGA	Resolution: 1920 × 1080P/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz,1024 × 768/60Hz
HD Output	Resolution: 1920 × 1080P/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz,1024 × 768/60Hz
Display Split	16 Channel/9 Channel/4 Channel / 1Channel
Privacy Masking	3 Rectangular Zones (Each camera)

OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording
<b>Recording</b>	
Video Compression	H.265/H.265+/H.264/H.264+
Audio Compression	G.711U/G.711A
Resolution	5MP(2592×1944),8MP_LITE(1920×2160),5MP_HALF(1296×1944),4MP(2560×1440),4MP_HALF(1280×1440), 3MP(2048×1536),3MP_Lite(1024×1536),1080P(1920×1080),720P(1280×720),960H(P:960×576/N:960×480)
Video Quality	Lowest/Low/Ordinary/Good/Better/Best
Record Rate	Normal Mode: Analog: PAL:8MP_LITE(1920×2160 4*8fps), 5MP(2592×1944 4*6fps), 5MP_HALF(1296×1944 4*10fps),4MP(2560×1440 4*8fps),4MP_HALF(1280×1440 4*15fps), 3MP(2048×1536 4*9fps),3MP_Lite(1024×1536 4*18fps), 1080P(1920x1080 4*15fps), 720P(1280×720 4*25fps), 960H(960×576 4*25fps) NTSC:8MP_LITE(1920×2160 4*8fps), 5MP(2592×1944 4*6fps),5MP_HALF(1296×1944 4*10fps), 4MP(2560×1440 4*8fps),4MP_HALF(1280×1440 4*15fps),3MP(2048×1536 4*9fps), 3MP_Lite(1024×1536 4*18fps), 1080P(1920x1080 4*15fps),720P(1280×720 4*25fps), 960H(960×480 4*25fps) Lite Mode: PAL:5MP_Lite(1296×1944 4*10fps),4MP_Lite(1280×1440 4*15fps),3MP_Lite(1024×1536 4*18fps), 1080N(960×1080 4*25fps),720P(1280×720 4*25fps), 960H(960×480 4*25fps) NTSC: 5MP_Lite(1296×1944 4*10fps),4MP_Lite(1280×1440 4*15fps),3MP_Lite(1024×1536 4*18fps), 1080N(960×1080 4*25fps),720P(1280×720 4*25fps), 960H(960×480 4*30fps) Pure IP(H.265): PAL: 5MP@8×25fps,4MP@12×25fps,3MP@12×25fps,1080P@16×25fps, 960P@16×25fps,720P@16×25fps,D1@16×25fps NTSC: 5MP@8×30fps,4MP@12×30fps,3MP@12×30fps,1080P@16×30fps, 960P@16×30fps, 720P@16×30fps, D1@16×30fps
Record Mode	Manual\Timer\Motion Detection\Alarm Input
<b>Playback &amp; Backup</b>	
Decode Capability	2CH 1080P@30fps
Sync Playback	Normal Mode: Pure Analog: 4CH 5M@6fps, 4CH 8M_Lite@8fps, 4CH 4M@8fps, 4CH 3M@9fps, 3CH 1080p@15fps Mix Mode: 1CH 5M@30fps, 1CH 4M@30fps, 1CH 3M@30fps, 2CH 1080P@30fps Pure IPC: 1CH 5MP@30fps, 1CH 4MP@30fps, 1CH 3M@30fps, 2CH 1080P@30fps Lite Mode: Pure Analog:4CH 5M_LITE@10fps,CH 4M_LITE@15fps,3M_LITE@18fps,4CH 1080N@25fps Mix Mode: 1CH 5M@30fps, 1CH 4M@30fps, 1CH 3M@30fps, 2CH 1080P@30fps Pure IPC: 1CH 5MP@30fps, 1CH 4MP@30fps, 1CH 3M@30fps, 2CH 1080P@30fps
Remote Playback	4 Channel / 1Channel
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast play, Slow play, Rewind, Single frame forward/back, Digital Zoom, Full screen
Smart Phone Playback	4 Channel
Backup Mode	USB Device(with format FAT 32 )/Network/FTP
<b>Network</b>	
Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTP, RTSP, RTCP
DDNS	Dyndns, changeip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE,HDPROVN
Web Browser	Edge,IE8-11, Google Chrome , Firefox ,Safari
CMS Software	Support Windows 7/ Windows 8/Windows 10
Extra Stream	CIF/D1(1-30fps)
Smart Phone	iPhone, ipad, Android ,Android pad
<b>Hard Disk Driver</b>	
Interface Type	1 SATA Interface
Capacity	1 SATA Hard Disk (2.5"/3.5" SATA, Up to 8TB)
<b>General</b>	
Language	Simplified Chinese,Traditional Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Japanese, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek, Vietnamese,
UTC Control	YES
USB Interface	2 USB 2.0 Interfaces
Power consumption	DC 12V/2A ≤6W (Without Hard Disk)
Working Environment	-10~55℃/10~90%
Dimension (W×D×H)	260*215*43(mm)

Weight	2kg (Without HDD)
--------	-------------------

**Cantonk (guangzhou) Corporation Limited**

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: [info@cantonk.com](mailto:info@cantonk.com)