



◆ SPECIFICATION

Model	PT4AH18XIGC200
Camera	
Image Sensor	1/2.9" Progressive Scan CMOS Sensor
Horizontal Resolution	2MP
Compression	H.264/H.265
S/N Ratio	60db
PTZ	
Horizontal Rotation Speed	120°/S
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	30°/S
Tilt Rotation Range	0°~93°
Preset Points	255
Guard Tours	8 groups
Guard Points	Max.20 points
Lens	
Focus Length	5.35-96.3mm F1.8-F3.9
Focus Control	18X Optical Zoom
Night Vision	
Infrared LED	∅ 35 x 6PCS
IR Range	80m
Day-night mode	AUTO
Network	
Network protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Main Stream1	1920*1080@30fps
Main Stream2	1280*720@30fps
Main Stream3	/
Sub Stream1	720*480@30fps
Sub Stream2	352*288@30fps
AI Function	
Smart Analytic	3D Human Tracking 、 Intrusion Detection 、 Alarm Detection
Tracking effective range	5~45M Speed: 3~12KM/h
Interface	
Audio	2-Way Audio
Alarm	/
SD Card Slot	Optional
POE	Optional
General	
Weatherproof	IP66
Operating Temperature	-40℃~+70℃
Operating Humidity	≤90% Non Condensing
Power	DC12V/3A
Lightning Protection	Transient voltage 6000V
Dimension	18.5x 18.5 x 28.8 (cm)
Weight	1.56Kgs

