



◆ SPECIFICATION

Model NO.	AC94
<b>Features</b>	
◆ Online firmware upgrade, synchronous update function and experience	
◆ intelligent push, filter out useless information	
◆ Support Android, IOS intelligent terminal remote real-time monitoring	
◆ Support alarm input and output control functions, can control strobe lights in linkage, and can also be used for linkage control of alarm equipment	
◆ 2.0mp HD Pixel (1920X1080), clear picture quality	
◆ Support preset point setting and recall function, support up to 6 preset points, support preset point cruise function	
◆ Support accurate humanoid tracking, and can set the guard position. After the target tracking is completed, it can automatically return to the guard position and wait for the next tracking.	
◆ Wired and wireless automatic switching, in the environment of poor wireless signal, you can directly use the wired connection device and router, automatically switch to wired mode	
◆ Support TF card recording and cloud recording, TF card supports up to 128G	
◆ Support cloud service, free 3-day cloud service experience package	
◆ Support two-way voice call function, module onboard power amplifier IC, can effectively eliminate echo, suppress noise, prevent distortion and other phenomena	
◆ Support device sharing function (support sharing multiple friends) and device management identity transfer function	
◆ Infrared night vision lighting (night vision distance 15 meters), 24-hour monitoring day and night, IR-CUT switching, no color cast during the day, and clearer night vision	
<b>Specifications</b>	
<b>Main Processor</b>	
SOC	ARM
<b>Image Sensor</b>	
Sensor	1/3" color CMOS sensor
Lens	M12, f: 4mm, F2.3, 3-megapixel
Visual angle	H (horizontal) 67 degrees; V (vertical) 50 degrees; D (diagonal) 88 degrees
Minimum illumination	0.01Lux
<b>Audio</b>	
Input/Output	Two-way voice intercom available (built-in Microphone and speaker)
Audio compression method	AAC

<b>Video</b>	
Video compression method	H.264/H.265
Lighting frequency	50Hz, 60Hz
Image frame rate	15fps
Maximum Image Resolution	1920*1080P
Light Source for Night Vision	IRCUT double filter automatic switching, 6 infrared lamps (850nm wavelength), irradiation distance:5 meters
<b>Network</b>	
Wireless Network	2.4G Wi-Fi (IEEE802.11b/g/n), built-in antenna
Protocols Supported	TCP/IP, UDP/IP, DHCP, RTMP, MUDP
IP Address Supported	Dynamic IP address supported
<b>AI</b>	
Intelligent function	Intelligent push, Humanoid detection, vehicle detection, package detection, pet capture, activity zone
<b>Alarm</b>	
Alarm detection	Motion Detection
Alarm linkage	Motion detection alarm, humanoid detection alarm, sound and light alarm, alarm video, snapshot
Alarm notification	Alarm push by mobile APP
<b>PTZ</b>	
PTZ rotation angle	H (horizontal) 0° ~ 355°; V (vertical) -20° ~ 90°
<b>Interface</b>	
Power Supply	1 Micro USB interface, DC 5V/1A
SD card	1 Micro SD card (up to 128GB)
Keys	1 function key
<b>Other</b>	
Adjustable lens	Not adjustable
LED indication	Monochrome white light (power/network signal/function indicator)
Video storage method	Micro SD card (up to 128GB) local storage, cloud storage
Install method	Ceiling or wall hanging
<b>Environment</b>	
Dustproof and waterproof	no
Operating environment	-10° ~ 45°C /10% ~ 80% (no condensation)
Storage environment	-20°C ~ 60° /0% ~ 90% (no condensation)
<b>Color</b>	
Appearance color	White
<b>Specification</b>	
Dimensions (L*W*H)	50*200*120mm
Net Weight of Bare Machine	677.9g
<b>Certification</b>	
Certificate	CE, FCC, RoHS

**Cantonk (Guangzhou) Corporation Limited**

Add.: Floor 1-3, Building 1, No. 18, Dongming 3rd Road, Huangpu District, Guangzhou, China

Tel. No.: +86 20 66217288

Fax No.: +86 20 66217166

Homepage: <http://www.cantonk.com>

Email: [info@cantonk.com](mailto:info@cantonk.com)